

## Technical Data Sheet

# Decorative coating TESORO

### Ready-made decorative coating

TESORO is a unique decorative coating for interior work. This product will perfectly fit into both classic and ultra-modern interiors. The specially developed color range of the coating is determined by the choice of the TESORO TONER colorant in combination with the metallized TESORO GOLD and TESORO SILVER pigments, which are simply added to the TESORO base. The colors of the dyes are selected so that you can get completely different and unusual solutions for your walls, such as imitation of rust, etching, copper oxidation and other metallized effects.

#### Properties:

depending on the application technique, it allows you to obtain various effects on the surface  
high strength  
changes shades depending on lighting and angle of view (in case of the use of metallized pigments)  
maintainable  
withstands cleaning with detergents  
hides surface preparation defects

#### Composition:

Substrate	acrylic copolymers
Pigment	mineral fillers and pigments
Reducer	water

#### Types of substrates:

The product is used for interior work. They are used for decorative finishing of surfaces made of gypsum, cement, lime-cement plaster, brick, concrete, gypsum fiber cement boards.

#### Surface preparation:

Before application, the surface must be solid, dry, free from dust, oil and grease. Places affected by mold and moss should be cleaned and mechanically treated with D 07 TM "Elf" soil or other special means. Apply TESORO PRIMER special primer to the prepared surface. Wait until it dries completely (4-5 hours).

#### Performance of works:

To get the color of the coating you like from the catalog, you need to add the selected TESORO TONER dye (100 ml) to the jar with the base of the TESORO decorative coating (2.5 l), and to get a golden or silver shimmer, add the metallized pigment TESORO GOLD or TESORO SILVER (250 ml), respectively, according to the recipe specified in the catalog. Stir the decorative coat gently.

**IMPORTANT:** it is not recommended to use a mixer for mixing, so as not to disturb the structure of the material.

Apply TESORO with a flat, wide, shortened brush in a crosswise motion from top to bottom, randomly distributing the material over the entire surface.

After 10-15 minutes, when the moisture stabilizes a little on the surface, crush the pigmented flakes with a metal small in multidirectional or circular movements with light pressure and distribute them over the surface, thus obtaining the desired decorative effect.

It is recommended to use VARNISH PROTECT varnishes as a reinforcement of the protective layer.

**Drying at a temperature of + 20 ° C and a relative humidity of 60%**

Touch-dry	8-12 hours
Complete drying out	24 hours
Recommended temperature conditions	from + 10 <sup>0</sup> C to + 30 <sup>0</sup> C

**Components**

water	25,00%
filler	55,00%
dispersion	15,00%
conserving agent	0,03%
anti-foaming agent	1,00%
auxiliary materials	3,97%

**Technical features:**

Coverage rate	base coat TESORO - 6 m <sup>2</sup> / l (15 m <sup>2</sup> / bottle)
Non-volatile matter content	60,00%
Solidity	1,12±0,05 kg/m <sup>3</sup>
Medium	acrylic copolymer
PH	7,0-9,0

**Recommendations:**

Precautions	In case of contact with eyes, rinse immediately with plenty of water.
Storage	In a dry and clean place at a temperature from +5 °C to + 30 <sup>0</sup> C, in a sealed package not less than 18 months from the date of manufacture
Packing	1 l, 2,5 l, 5 l

**ATTENTION:**

The firm is not responsible for poor-quality results (the occurrence of coating defects) in case of improper application on inappropriate places and surfaces, at the change of conditions of use, as well as the occurrence of a larger expense at using by not recommended methods